

# Contact-less Drinking Fountain & Under Sink Chiller

With Contact-Less Swan Neck Tap

The FONT10CL and UC800CL are complete with a contact-less Swan Neck Tap to avoid hand to tap bacterial contamination

## FONT 10CL

FONT10CL Wall Mounted Drinking Fountain with Infra Red Sensor for indoor and covered outdoor areas



## UC800CL

UC800CL Under sink Chiller with Infra Red Sensor



## Description

- The Infra Red Sensor is activated by a hand hovering over the sensor at a distance of 2cm to 5cm. The Sensor is connected to an Inlet Solenoid which opens the water supply when activated, and stops the water flowing when the hand is removed.
- The UC800CL has a cold water capacity of 5 ltr/h with an instant draw off of 1.5ltr below 10°C, from an influent temperature of 26°C. Fan assisted cooling and with an integral pressure arrestor to release pressure build up in the chilling unit. Must be installed in a well ventilated area, to avoid malfunctioning.
- The FONT10CL provides ambient water. It can be connected to an Under-sink Chiller to provide chilled water.



**AA**  
FIRST  
WATER COOLERS  
& BOILERS



refreshingly different

# GLASSFILLER CL

Contact-Less Swan Neck Tap

The GLASSFILLER CL Is Available As An Accessory

Impressive 23cm  
Dispensing Height

Infra Red Sensor



## Description

- The GLASSFILLER CL Infra Red Sensor is activated by a hand hovering over it at a distance of 2cm – 5cm
- It is connected to an inlet solenoid which opens the water supply to the tap as the hand hovers over the sensor. If you remove the hand, the dispensing will stop
- The Inlet Solenoid is powered by 2 x 6V batteries that have a tested life span of 300.000 activations
- The GLASSFILLER CL is programmed to stop dispensing after 6 seconds. If that is insufficient to fill your glass or bottle, place your hand again over the sensor to continue dispensing

**AAFIRST**  
WATER COOLERS  
& BOILERS

[www.aafirst.co.uk](http://www.aafirst.co.uk)

## Accessories For The UC800CL & FONT10CL

Description	Dimensions (mm) (H x W x D)	Weight (KG)
UC800CL	290 X 410 X 210	12.5
FONT10CL	220 X 310 X 345	2.7
GLASSFILLER CL	300H	-



Filter Housing  
With Carbon Block  
Candle &  
Nanofilter.



Installation Rail  
With Filter. Includes  
Compression Fitting,  
1-Micron Green  
Filter, Water Block,  
Copper Pressure  
Reducing Valve &  
Non-Return Valve.