

EZYTAP75 & EZYTAP7800

Elegant, Reliable, Under Counter Boiler For
Hot & Ambient Water Or Hot & Chilled Water



Features

The EZYTAP75/75T is a powerful undercounter hot water boiler which dispenses 14ltr/hour of 95°C hot water. It also dispenses copious amounts of un-chilled water.

The EZYTAP7800/7800T combines the powerful undercounter boiler with an undercounter chiller which dispenses 11.5ltr/hour of chilled water between 6 – 10°C. The Chilled water displaces the un-chilled water dispensed from the tap.

The EZYTAP is available with two different taps, that have different dispensing heights. The EZYTAP75/7800 has a dispensing height of 18.5cm. The EZYTAP75T/7800T has a dispensing height of 24cm.

Unique boiler scale protection in hard water areas.

The South and Central areas of England are known for high levels of scale – the enemy of boilers! Unlike other tap boilers the EZYTAP has two separate mains water connections. One for the boiler and the other for the ambient supply or the chilling unit. In hard water areas the boiler can be connected to a proper Scale Removal Filter and the ambient or chilling to a cheaper carbon filter. This arrangement extends the life of the Scale Removal Filter significantly. In a soft water area, both the boiler and chiller can be connected to a joint single carbon filter.

Attention: only proper scale removal filters will protect a boiler from scale and eliminate the need for constant descaling.

EZYTAP75 EZYTAP7800

EZYTAP75/7800
Dispensing Height Of 18.5cm



EZYTAP75T EZYTAP7800T

EZYTAP75T/7800T
Dispensing Height Of 24cm



Quality - Reliability - Integrity

EZYTAP75 EZYTAP7800

EZYTAP75T EZYTAP7800T

Elegant, Reliable, Under Counter Boiler For
Hot & Ambient Water Or Hot & Chilled Water

Description

Tap

- Chrome faucet with electronic controls
- Touch control dispensing taps
- Flashing indicator light when heating
- Hot water safety tap
- Dispensing height: EZYTAP75/7800 - 18.5cm
EZYTAP75T/7800T - 24cm



Under sink Boiler and Chiller unit

- The EZYTAP Boiler is an atmospheric boiler with a powerful 2KW SUS316 ring type heating element.
- The EZYTAP75/75T dispenses 14ltr/hour of 95°C hot water and copious amounts of un-chilled water
- The EZYTAP7800/T dispenses hot and chilled water. It includes our UC800M Undersink Chiller, which provides 11.5ltr/hour of chilled water between 6 – 10°C
- The UC800M Undersink Chiller is a compressor chilled cooler.
- The EZYTAP Boiler and the UC800M chiller units must be installed with 5cm ventilation space all round, to avoid over-heating.

Drip Tray

- EZYTRAY2: Drip tray connects to the EZYTAP column

Scale protection

- The two separate mains water inlets allow for the installation of a scale removal filter on the boiler inlet and a much more cost-effective taste, odour and turbidity carbon block filter on the ambient/chilled side
- Scale removal filters are expensive and since their effective 'life' is measured in litres of water passing through it, it is important to use it only on the boiler side
- Soft water areas only require a single carbon filter connected to a combined boiler and ambient/chilled inlet
- The sealed EZYAP Boiler can only be descaled by pushing descaling solution into the Tank, and leave it there to work for 30/40 minutes. See our Information Hub Issue 10 for more detailed descaling instruction.

Venting Pressure from the UC800M Chiller

- Ice can build up in the UC800M Undersink Chiller. This will result in an increase of pressure in the sealed chilling system which can lead to a failure of fittings and pipework which would result in a leak. It is therefore strongly recommended that the Safety Valve Kit, which comes with the UC800M, is installed. It vents any pressure building up into a

Specifications and performance

Model	Dispensing Height	Hourly output			Dimensions (mm)	Temp
		Hot	Ambient	Chilled		
EZYTAP75	18.5cm	14ltr	indefinite	n/a	329h, 220w, 352d	95°C max
EZYTAP75T	24cm	14ltr	indefinite	n/a	329h, 220w, 352d	95°C max
EZYTAP7800	18.5cm	14ltr	n/a	11.5ltr	Boiler 329h, 220w, 352d Chiller 300H, 410W, 300D	95°C max 6 – 10°C
EZYTAP7800T	24cm	14ltr	n/a	11.5ltr	Boiler 329h, 220w, 352d Chiller 300H, 410W, 300D	95°C max 6 – 10°C