

# EZYTAP85 & EZYTAP8800

## with NEW 8 Liter Hot Tank

The new high capacity 8 Liter Hot Tank provides 28 liters of steaming hot water per hour with an Instant Draw off of 7 ltrs at 95C+

It also includes a Sleep Mode function to save your customer Electricity and reduces the EZYTAP's Carbon production.

The EZYTAP85/8800 is a powerful Boiler, which Saves your customer Money and is Green in the process.



Installed with EZYTRAY 2

**EZYTAP85**  
**EZYTAP8800**

Dispensing Height Of 18.5cm



Installed with EZYTRAY 3

**EZYTAP85T**  
**EZYTAP8800T**

Dispensing Height Of 24cm

### Features

- The EZYTAP85/85T and the EZYTAP8800/8800T are powerful undercounter boilers which produce 28ltr/ hour of 95C hot water with an Instant Draw off of 7liters. They also dispense copious amounts of ambient water.
- The EZYTAP85 and 8800 has a dispensing height of 18.5cm. The dispensing height of the EAYTAP85T/EZYTAP8800T is 24cm – ideal to fill sport bottles.
- All EZYTAPS can be connected to our Undercounter Chiller (UC800M) which produces 11.5ltrs per hour of between 6 – 10C water. The chilled water replaces the un-chilled water dispensed from the Tap.

Unique boiler scale protection in hard water areas.

The South and Central areas of England are known for high levels of scale – the enemy of boilers! Unlike other tap boilers the EZYTAP has two separate mains water connections. One for the boiler and the other for the ambient supply or the chilling unit. In hard water areas the boiler can be connected to a proper Scale Removal Filter and the ambient or chilling to a cheaper carbon filter. This arrangement extends the life of the Scale Removal Filter significantly. In a soft water area, both the boiler and chiller can be connected to a joint single carbon filter

Attention: only proper scale removal filters will protect a boiler from scale and eliminate the need for constant descaling.

## EZYTAP85 EZYTAP8800

## EZYTAP85T EZYTAP8800T

The EZYTAP85/8800 is a powerful Boiler, which Saves your customer Money and is Green in the process.

## Description

### TAP

- Chrome faucet with electronic controls
- Touch control dispensing taps
- Flashing indicator light when heating
- Hot water safety tap
- Dispensing height: EZYTAP85/8800 - 18.5cm  
EZYTAP85T/8800T - 24cm
- Sleep mode option to save electricity and reduce carbon production.

### UNDERSINK BOILER & CHILLER UNIT

- The EZYTAP85/8800 is a powerful 8 liter Boiler. It dispenses 28ltr/hour of 95C+ boiling water, with an instant draw off of 7ltr
- The EZYTAP dispenses hot and ambient water.
- It can be connected to an Undersink chiller (UC800M) to provide 11.5 ltr/hour of chilled water between 6 – 10C. The chilled water replaces the ambient water dispensed from the Tap.
- The UC800M Undersink chiller is a compressor chilled cooler.
- The EZYTAP Boiler and the Undersink chiller must be installed with 5cm ventilation space all round, to avoid over-heating.

### DRIP TRAYS

- The EZYTRAY2 & EZYTRAY3 are not part of the EZYTAP and can be purchased separately. The EZYTRAY2/3 come with an Installation Template and a drain away kit which includes a 1m length 22mm internal diameter waste pipe to connect to waste.

### SCALE PROTECTION

- The two separate mains water inlets allow for the installation of a scale removal filter on the boiler inlet and a much more cost-effective taste, odour and turbidity carbon block filter on the ambient/chilled side
- Scale removal filters are expensive and since their effective 'life' is measured in litres of water passing through it, it is important to use it only on the boiler side
- Soft water areas only require a single carbon filter connected to a combined boiler and ambient/chilled inlet
- The EZYTAP boiler can be opened for descaling and servicing?
- See our Information Hub Issue 10 for more detailed descaling instruction.



### VENTING PRESSURE FROM THE UC800M CHILLER


- Ice can build up in the UC800M Undersink Chiller. This will result in an increase of pressure in the sealed chilling system which can lead to a failure of fittings and pipework which would result in a leak. It is therefore strongly recommended that the Safety Valve Kit, which comes with the UC800M, is installed. It vents any pressure building up into a sink drain or a waste container.

### HEATING STATUS

- Flashing "H" means heating.
- Non-flashing "H" means ready for use.

### SAFETY / HOT

- Press safety and then hot to turn on hot water.



### POWER / SLEEP

- Press & hold for 6 seconds to turn the power on.
- When the power is on, press button one time to enter sleep mode. The unit will stop heating for 6 hours.

### COLD

- Press "Ambient/Chilled" to turn cold water on.

## Specifications and performance

Model	Dispensing Height	Hourly output			Dimensions (mm)	Temp
		Hot	Ambient	Chilled		
EZYTAP85	18.5cm	28ltr	indefinite	n/a	329h, 220w, 352d	95°C max
EZYTAP85T	24cm	28ltr	indefinite	n/a	329h, 220w, 352d	95°C max
EZYTAP8800	18.5cm	28ltr	n/a	11.5ltr	Boiler 329h, 220w, 352d	95°C max
					Chiller 300H, 410W, 300D	6 – 10°C
EZYTAP8800T	24cm	28ltr	n/a	11.5ltr	Boiler 329h, 220w, 352d	95°C max
					Chiller 300H, 410W, 300D	6 – 10°C